

### SECTION 1: Identification

#### 1.1. Identification

Product form : Mixture  
Product name : Roofing Liquid Polymer with SigmaBond  
Synonyms : USP 2852, USP 2550, USP 2150, USP 2850

#### 1.2. Recommended use and restrictions on use

Recommended use : Building and construction work  
Restrictions on use : None known

#### 1.3. Supplier

US Polyco, Inc.  
3901 South I-45  
Ennis, TX 75119  
T 972-875-9300

#### 1.4. Emergency telephone number

Emergency number : Chemtrec 1-800-424-9300

### SECTION 2: Hazard(s) identification

#### 2.1. Classification of the substance or mixture

##### GHS US classification

Skin corrosion/irritation Category 2	H315	Causes skin irritation
Serious eye damage/eye irritation Category 2A	H319	Causes serious eye irritation
Skin sensitization, Category 1	H317	May cause an allergic skin reaction
Carcinogenicity Category 2	H351	Suspected of causing cancer
Full text of H statements : see section 16		

#### 2.2. GHS Label elements, including precautionary statements

##### GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) : Warning

Hazard statements (GHS US) : H315 - Causes skin irritation  
H317 - May cause an allergic skin reaction  
H319 - Causes serious eye irritation  
H351 - Suspected of causing cancer

Precautionary statements (GHS US) : P201 - Obtain special instructions before use.  
P202 - Do not handle until all safety precautions have been read and understood.  
P261 - Avoid breathing dust/fume/gas/mist/vapors/spray.  
P264 - Wash hands, forearms and face thoroughly after handling.  
P272 - Contaminated work clothing must not be allowed out of the workplace.  
P280 - Wear protective gloves/protective clothing/eye protection/face protection.  
P302+P352 - If on skin: Wash with plenty of water.  
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

# Roofing Liquid Polymer with SigmaBond

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P308+P313 - If exposed or concerned: Get medical advice/attention.  
P321 - Specific treatment (see supplemental first aid instruction on this label).  
P332+P313 - If skin irritation occurs: Get medical advice/attention.  
P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.  
P337+P313 - If eye irritation persists: Get medical advice/attention.  
P362+P364 - Take off contaminated clothing and wash it before reuse.  
P363 - Wash contaminated clothing before reuse.  
P405 - Store locked up.  
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

### 2.3. Other hazards which do not result in classification

No additional information available

### 2.4. Unknown acute toxicity (GHS US)

Not applicable

## SECTION 3: Composition/Information on ingredients

### 3.1. Substances

Not applicable

### 3.2. Mixtures

Name	Product identifier	%	GHS US classification
Mixture of asphalt, tire rubber, and related compounds*	CAS-No.: Trade Secret	0-70	Skin Irrit. 2, H315 Eye Irrit. 2A, H319 Skin Sens. 1A, H317 Carc. 2, H351
Rubber, natural	CAS-No.: 9006-04-6	5 – 20	Skin Sens. 1, H317
Carbon black	CAS-No.: 1333-86-4	0 – 8	Carc. 2, H351
Hydrogen sulfide	CAS-No.: 7783-06-4	< 7	Flam. Gas 1, H220 Acute Tox. 2 (Inhalation:gas), H330 Aquatic Acute 1, H400
Zinc oxide (ZnO)	CAS-No.: 1314-13-2	0 – 1	Aquatic Acute 1, H400 Aquatic Chronic 1, H410

\*Chemical name, CAS number and/or exact concentration have been withheld as a trade secret

Full text of hazard classes and H-statements : see section 16

## SECTION 4: First-aid measures

### 4.1. Description of first aid measures

First-aid measures general : IF exposed or concerned: Get medical advice/attention.  
First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.  
First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.  
First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.  
First-aid measures after ingestion : Call a poison center/doctor/physician if you feel unwell.

# Roofing Liquid Polymer with SigmaBond

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### 4.2. Most important symptoms and effects (acute and delayed)

Symptoms/effects after skin contact : Irritation. May cause an allergic skin reaction.  
Symptoms/effects after eye contact : Eye irritation.

### 4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

## SECTION 5: Fire-fighting measures

### 5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam.  
Unsuitable extinguishing media : Not determined.

### 5.2. Specific hazards arising from the chemical

Hazardous decomposition products in case of fire : Toxic fumes may be released.

### 5.3. Special protective equipment and precautions for fire-fighters

Firefighting instructions : Fight fire with normal precautions from a reasonable distance.  
Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapors/spray.

#### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Mechanically recover the product. Notify authorities if product enters sewers or public waters.  
Other information : Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear personal protective equipment. Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapors/spray.

# Roofing Liquid Polymer with SigmaBond

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store locked up. Store in a well-ventilated place. Keep cool.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

Roofing Liquid Polymer with SigmaBond	
No additional information available	
Mixture of asphalt, tire rubber, and related compounds	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	0.5 mg/m <sup>3</sup> (fume, inhalable particulate matter)
ACGIH chemical category	Not Classifiable as a Human Carcinogen fume, coal tar-free
USA - ACGIH - Biological Exposure Indices	
BEI (BLV)	2.5 µg/l Parameter: 1-Hydroxypyrene with hydrolysis - Medium: urine - Sampling time: end of shift at end of workweek (background) Parameter: 3-Hydroxybenzo(a)pyrene with hydrolysis - Medium: urine - Sampling time: end of shift at end of workweek (nonquantitative)
Zinc oxide (ZnO) (1314-13-2)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	2 mg/m <sup>3</sup> (respirable particulate matter)
ACGIH OEL STEL	10 mg/m <sup>3</sup> (respirable particulate matter)
USA - OSHA - Occupational Exposure Limits	
OSHA PEL TWA	5 mg/m <sup>3</sup> (fume) 15 mg/m <sup>3</sup> (total dust) 5 mg/m <sup>3</sup> (respirable fraction)
Hydrogen sulfide (7783-06-4)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	1 ppm
ACGIH OEL STEL	5 ppm
USA - OSHA - Occupational Exposure Limits	
OSHA PEL (Ceiling)	20 ppm
Acceptable maximum peak above the acceptable ceiling concentration for an 8-hr shift	50 ppm Peak (10 minutes once, only if no other measurable exposure occurs)
Carbon black (1333-86-4)	
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	3 mg/m <sup>3</sup> (inhalable particulate matter)
ACGIH chemical category	Confirmed Animal Carcinogen with Unknown Relevance to Humans

# Roofing Liquid Polymer with SigmaBond

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Carbon black (1333-86-4)

#### USA - OSHA - Occupational Exposure Limits

OSHA PEL TWA	3.5 mg/m <sup>3</sup>
--------------	-----------------------

### Rubber, natural (9006-04-6)

#### USA - ACGIH - Occupational Exposure Limits

ACGIH OEL TWA	0.0001 mg/m <sup>3</sup> (inhalable particulate matter)
---------------	---

ACGIH chemical category	Skin - potential significant contribution to overall exposure by the cutaneous route, dermal sensitizer
-------------------------	---

### 8.2. Appropriate engineering controls

Appropriate engineering controls	: Ensure good ventilation of the work station.
Environmental exposure controls	: Avoid release to the environment.

### 8.3. Individual protection measures/Personal protective equipment

#### Hand protection:

Protective gloves

#### Eye protection:

Safety glasses

#### Skin and body protection:

Wear suitable protective clothing

#### Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment

#### Personal protective equipment symbol(s):



## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Solid
Appearance	: Solid. Semi-solid.
Color	: Black Brown
Odor	: Slight
Odor threshold	: No data available
pH	: No data available
Melting point	: No data available
Freezing point	: Not applicable
Boiling point	: No data available
Flash point	: > 260 °C
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability	: Non flammable.
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available

# Roofing Liquid Polymer with SigmaBond

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Relative density	: No data available
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: Not applicable
Decomposition temperature	: No data available
Viscosity, kinematic	: Not applicable
Viscosity, dynamic	: No data available
Explosion limits	: Not applicable
Explosive properties	: No data available
Oxidizing properties	: No data available

### 9.2. Other information

No additional information available

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified.
Acute toxicity (dermal)	: Not classified.
Acute toxicity (inhalation)	: Not classified.

Mixture of asphalt, tire rubber, and related compounds	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rabbit	> 2000 mg/kg
Zinc oxide (ZnO) (1314-13-2)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rat	> 2000 mg/kg
LC50 Inhalation - Rat	> 5700 mg/m <sup>3</sup> (Exposure time: 4 h)

# Roofing Liquid Polymer with SigmaBond

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hydrogen sulfide (7783-06-4)	
LC50 Inhalation - Rat [ppm]	501 ppm/4h
ATE US (gases)	100 ppmV/4h

Carbon black (1333-86-4)	
LD50 oral rat	> 15400 mg/kg

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified.
Carcinogenicity	: Suspected of causing cancer.

Mixture of asphalt, tire rubber, and related compounds	
IARC group	2B - Possibly carcinogenic to humans
In OSHA Hazard Communication Carcinogen list	Yes

Carbon black (1333-86-4)	
IARC group	2B - Possibly carcinogenic to humans
In OSHA Hazard Communication Carcinogen list	Yes

Reproductive toxicity	: Not classified.
STOT-single exposure	: Not classified.
STOT-repeated exposure	: Not classified.
Aspiration hazard	: Not classified.
Viscosity, kinematic	: Not applicable
Symptoms/effects after skin contact	: Irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Eye irritation.

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.
-------------------	--

Zinc oxide (ZnO) (1314-13-2)	
LC50 - Fish [1]	1.55 mg/l (Exposure time: 96 h - Species: Danio rerio [static])

Hydrogen sulfide (7783-06-4)	
LC50 - Fish [1]	0.0448 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [flow-through])
LC50 - Fish [2]	0.016 mg/l (Exposure time: 96 h - Species: Pimephales promelas [flow-through])

### 12.2. Persistence and degradability

No additional information available

### 12.3. Bioaccumulative potential

Mixture of asphalt, tire rubber, and related compounds	
BCF - Fish [1]	(no bioaccumulation expected)
Partition coefficient n-octanol/water (Log Pow)	> 6

# Roofing Liquid Polymer with SigmaBond

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### Hydrogen sulfide (7783-06-4)

BCF - Fish [1]	(no bioaccumulation expected)
Partition coefficient n-octanol/water (Log Pow)	0.45 (at 25 °C)

### 12.4. Mobility in soil

No additional information available

### 12.5. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Disposal methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

## SECTION 14: Transport information

In accordance with DOT / IMDG / IATA

### 14.1. UN number

Not regulated for transport

### 14.2. UN proper shipping name

Proper Shipping Name (DOT) : Not applicable  
Proper Shipping Name (TDG) : Not applicable  
Proper Shipping Name (IMDG) : Not applicable  
Proper Shipping Name (IATA) : Not applicable

### 14.3. Transport hazard class(es)

**DOT**  
Transport hazard class(es) (DOT) : Not applicable

**IMDG**  
Transport hazard class(es) (IMDG) : Not applicable

**IATA**  
Transport hazard class(es) (IATA) : Not applicable

### 14.4. Packing group

Packing group (DOT) : Not applicable  
Packing group (IMDG) : Not applicable  
Packing group (IATA) : Not applicable

### 14.5. Environmental hazards

Other information : No supplementary information available.

### 14.6. Special precautions for user

**DOT**  
No data available



# Roofing Liquid Polymer with SigmaBond

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

### IMDG

No data available

### IATA

No data available

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

#### Roofing Liquid Polymer with SigmaBond

SARA Section 311/312 Hazard Classes	Health hazard - Carcinogenicity Health hazard - Respiratory or skin sensitization Health hazard - Serious eye damage or eye irritation Health hazard - Skin corrosion or Irritation
-------------------------------------	--

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory, except for:

Rubber, natural	CAS-No. 9006-04-6	5 – 20%
-----------------	-------------------	---------

Chemical(s) subject to the reporting requirements of Section 313 or Title III of the Superfund Amendments and Reauthorization Act (SARA) of 1986 and 40 CFR Part 372.

Hydrogen sulfide	CAS-No. 7783-06-4	< 7%
------------------	-------------------	------

#### Hydrogen sulfide (7783-06-4)

CERCLA RQ	100 lb
Section 302 EPCRA Reportable Quantity (RQ)	100 lb
SARA Section 302 Threshold Planning Quantity (TPQ)	500 lb

### 15.2. International regulations

#### Mixture of asphalt, tire rubber, and related compounds

Listed on IARC (International Agency for Research on Cancer)

#### Carbon black (1333-86-4)

Listed on IARC (International Agency for Research on Cancer)

### 15.3. US State regulations



**WARNING:**

This product can expose you to Carbon black, which is known to the State of California to cause cancer. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

# Roofing Liquid Polymer with SigmaBond

## Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Component	State or local regulations
Mixture of asphalt, tire rubber, and related compounds()	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right To Know List
Zinc oxide (ZnO)(1314-13-2)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right To Know List; U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
Hydrogen sulfide(7783-06-4)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right To Know List; U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List
Carbon black(1333-86-4)	U.S. - New Jersey - Right to Know Hazardous Substance List; U.S. - Pennsylvania - RTK (Right to Know) List; U.S. - Massachusetts - Right To Know List

### SECTION 16: Other information

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Revision date : 02/06/2024

Full text of H-phrases	
H220	Extremely flammable gas
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H330	Fatal if inhaled
H351	Suspected of causing cancer
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects

Safety Data Sheet (SDS), USA - HSI

DISCLAIMER OF LIABILITY The information in this SDS was obtained from sources which we believe are reliable. However, the information is provided without any warranty, express or implied, regarding its correctness. The conditions or methods of handling, storage, use or disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. This SDS was prepared and is to be used only for this product. If the product is used as a component in another product, this SDS information may not be applicable